

## create the outdoor room

Aluxor's awnings add charm to any setting while providing a perfect indoor outdoor environment for entertaining, day or night.

The Aluxor Eco is a classical awning that protects against the sun or light rain as well as creating a cosy and private ambience. Ideal for patios, verandahs, balconies and restaurants, the retractable roof system creates a large pavilioned space free of structures and poles.

For installations that are well protected, such as under roof eaves, the Aluxor Eco is an ideal awning for home or retail applications. Where additional protection is required the awning can be fitted with an extruded aluminium pelmet to your choice of colour.

Using German designed and manufactured systems the operation can be set at any angle up to a pitch of 35°.

The Aluxor Eco is available in three popular colours of white, silver and cream in sizes up to 6m wide by 3m projection. Optional pelmet is available in six colours of white, silver, cream, black, beige or dark grey. Operation can be manual or motorised.









All operating components are designed and manufactured in Germany and certified by international testing agency TÜV to the European standard 'CE Marking'.

The Secuflex 50 folding arms use tensioned, spring loaded, PVC coated twin cables that provide added protection against corrosion. These cables are individually hung to provide excellent wind stability and fabric tension.



The Secuflex 50 folding arms are able to withstand 120,000 cycles of stress, as certified by Materials Testing Authority of Germany.

Patented pivot ball front bar connector provides the best possible operational safety.

Extruded aluminium profiles for pelmets and cassettes provide solid, stable and long lasting quality that will not rust or vibrate in harsh conditions.



Powdercoated galvanised steel support bars have a high durability epoxy undercoat, Pacesetter HP200, 160 microns thick to provide additional anti-corrosion protection.









## Specifications

Dimensions (h x d) Dimensions pelmet (h x d) Width single unit Projection range Standard frame Aluminium pelmet

Operating mechanism Automation features

- 215 x 130mm
- A 245 x 195mm
- 2m 6m
- 1.5m 3m
- ✓ White, silver or cream powdercoated
- A White, silver, cream, beige, black or dark grey colours powdercoated
- Acrylic canvas with valance
- Manual
- Remote operated motor

## Your Authorised Distributor is:



conditions apply