

Curtain Track

A smart product for a smart home

Product benefits:

- Smooth, quiet and fast operation
- User friendly
- Auto commissioning function – sets it's own limits – simple & time saving
- Auto open and close when the curtain fabric is drawn by hand
- Manual over-ride when power is off – recommissions automatically when powered on again
- Integrates on all Motolux controls, so can be used with Motolux roller, roman and cellular blind motor systems – see more information on the controls [here](#)
- 240v power – no transformers required
- Dry contact input for easy integration with automation systems (C-Bus, Dynalite)
- Remote and Automation system simultaneous control possible
- Tandem configuration possible
- Five year manufacturer's warranty

Mounting and installation:

- Maximum curtain width 12 metres (39feet) using track joiners
- Track is bendable to minimum radius 350mm (14") right angle bend
- Suitable for light to heavy weight curtains up to 90kg (198lbs) fabric weight
- Suitable for either wall mount (with installation bracket) or top fixing using butterfly clips

Safety features:

- Overload and over-temperature protection in-built

RF Features

- Fully electronic programming and operation
- Radio remote control handset or fixed wall switch
- Automation system compatible as standard, including simultaneous use of remote control
- Easy programming with independent setting of channels and limits
- Remote operation up to 30 metres (100feet)inside buildings and up to 100 metres (300 feet) in open areas
- Individual or group motor control, with up to 11 channels per remote and 24 channels per motor

